Solrain



NEW GENERATION
Solar Pro Collection

Sauleda

SOLRAIN

Solrain are all-purpose acrylic fabrics adapted to withstand extreme exposure both to sun and rain. Water repellency 1.000 mm.
Solrain es el tejido todo terreno adaptado para resistir tanto el sol como la lluvia. Cuenta con una columna de agua de 1.000 mm.




Solrain represents the new generation of all-purpose acrylic fabrics. Adapted to withstand extreme exposure to both sun and rain.

Its UV protection factors and high water column give it all the qualities required of a canvas for outdoor uses.
As a result, it is a fabric that offers many different possibilities and solutions in the following fields: outdoor stands, pagodas, reception marquees, restaurant awnings, terraces, grandstand canopies, ... and in general in any situation that needs extra protection from the rain, and also from excess sun and heat.

Solrain representa la nueva generación de tejidos acrílicos todo terreno. Adaptados para soportar tanto las inclemencias del sol como de la lluvia.

Sus índices de protección UV y su elevada columna de agua le confieren todas las cualidades que deben exigirse a una lona cuya aplicación este ubicada en la intemperie.
Solrain ofrece múltiples posibilidades y soluciones en los siguientes campos: stands exteriores, pagodas, carpas de recepción, carpas de restaurantes, terrazas, cubiertas de tribunas.... y en general en todas aquellas situaciones dónde sea necesario añadir una salvaguarda para la lluvia además de una protección solar y térmica.



Vertical awning ships · Drop arm awnings · Verandah awnings Sunshades · Outdoor vellum · Pergolas · Oudoor awnings · Roller shades

Toldo bandas verticales · Toldo punto recto · Toldo veranda · Parasol Velum exterior · Pergolas · Toldos exteriores · Bambalina enrollable

SOLRAIN

Fabric/ Material		Masacril® 100% Solution Dyed Acrylic Masacril® 100% Acrílico Tintado en Masa
Yarns/ Hilos	**Warp** Urdimbre	31 h/cm (Nm 34/2)
	Weft Trama	15 h/cm (Nm 34/2)
Tensile Strength Resistencia de tracción	**Warp** Urdimbre	150 daN/5 cm
	Weft Trama	95 daN/5 cm
Weight/ Peso		330 gr/m²
Water Repellency/ Columna de agua		1.000 mm
Finish/ Acabado		Sauleda Fabric Protector
Length of rolls/ Longitud de piezas		50 m / 60 m
Width/ Ancho		120 cm 47" | 153 cm 60" | 200 cm 78"

masacril® EXCLUSIVA FIBRA ACRÍLICA · EXCLUSIVE ACRYLIC FIBER
CERTIFIED ISO 9001
FABRIC PROTECTOR
OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100



SR Marfil
8272 ☼ UV 40



SR Beige
8267 ☼ UV 80



SR Coco
2047 ☼ UV 80



SR Integral
1550 new ☼ UV 80



SR Siroco
2075 ☼ UV 60



SR Café
2422 ☼ UV 80



SR Amarillo
8265 ☼ UV 80



SR Rojo
8277 ☼ UV 80



SR Brasserie
1551 new ☼ UV 80



SR Granate
8270 ☼ UV 80



SR Azul Real
8276 ☼ UV 80



SRAzul
8266 ☼ UV 80



SR Marino
8273 ☼ UV 80



SR Verde
8280 ☼ UV 80



SR Botella
8269 ☼ UV 80



SR Gris
8271 ☼ UV 80



SR Tweed Negro
2085 ☼ UV 80



SR Negro
8275 ☼ UV 80



SR Antracita
1552 new ☼ UV 80



Water Repellent
Repelente al agua



SR Leo 24 cm
8287 ☼ UV 60



SR Siena 24 cm
8291 ☼ UV 60



SR Nevada 30 cm
8288 ☼ UV 80



SR Iguana 30 cm
1553 new ☼ UV 80



SR Sand X 20 cm
1554 new ☼ UV 60




SR Kansas 30 cm
8286 ☼ UV 80



SR Arizona 30 cm
8285 ☼ UV 60



SR Aries 24 cm
8284 ☼ UV 60



SR Jalisco 23 cm
1555 new ☼ UV 80



SR Carbon X 20 cm
1556 new ☼ UV 80

Sauleda

Travessera de les Corts, 102 08028 Barcelona (Spain)

+34 933 397 150
sauleda@sauleda.com



@sauledatextiles

www.sauleda.com

© Sauleda, S.A. 2019. All rights reserved. Reproduction of any part of this publication is strictly forbidden without written permission from the publisher (including all logos, titles and graphic elements).

Sauleda
Tel: +34 93 339 71 50 Fax: +34 93
Email: sauleda@sauleda.com
www.sauleda.com

Solrain

FICHA TÉCNICA TECHNICAL FEATURES	**RESULTADOS** RESULTS	**ENSAYO** ESSAY
MATERIAL RAW MATERIAL	Acrilico 100% / Acrylic 100% Masacril tintado en masa Solution Dyed Masacril	
HILOS YARN **URDIMBRE**/WARP **TRAMA**/WEFT	 30cm (Nm 34/2) 15cm (Nm 34/2)	 UNE EN 1049.2
PESO WEIGHT	330g / m2	UNE EN 12127
RESISTENCIA TRACCION TENSIBLE STRENGTH **URDIMBRE**/WARP **TRAMA**/WEFT	 140daN / 5cm 95daN / 5cm	 UNE EN 1394.1
COLUMNA AGUA WATER COLUMN	1000 mm	UNE EN 20811
ANCHO WIDTH	120cm / 47"	
ACABADO FINISH	Sauleda PROTECTION	
LONGITUD PIEZAS ROLL LENGTH	60 ml	
SOLIDEZ A LA LUZ LIGHT FASTNESS	6 - 8	

Todos los valores pueden variar según una tolerancia de +/- 5% Utilización: lona para toldos - La lona Masac con los requisito de la norma EN 13561 (punto 15,2 tejidos) - Garantía 10 años de cualquier defecto imputable que se demuestre que el mantenimiento ha sido el correcto - Nota: los valores y tolerancias de este documer corresponden a nuestro nivel actual de conocimiento, experiencia de muchas producciones y se refieren al m su estado original. Son orientativos y no tienen ninguna validez legal. El cliente no está exento de probar si el apropiado a su aplicación.

Sauleda S.A. se reserva el derecho de modificar esta ficha técnica cuando lo crea oportuno.

CONFIDENCE IN TEXTILES

FABRIC PROTECTOR